

ANCHORING CLAMPS FOR ADSS ROUND CABLE – ACADSS

Description

The ACADSS clamps are used for the anchoring of 9mm to 19mm aerial round ADSS cables on distribution networks where spans do not exceed 90m.

These clamps consist of a thermoplastic conical body, a pair of wedges and an insulated flexible bail. All parts are captive. All plastic parts are UV-resistant



REF	MODEL	Ø CABLE	MATERIAL	MIN. BREAKING LOAD*
FC 318	ACADSS 10	9-12 mm	UV protected thermoplastic and stainless	600 daN
FC 319	ACADSS 12	11-14 mm		

Features

- Simple, fast and tool-less installation.
- Effective clamping of the cable by conical wedging.
- Installation without bending of the optical cable in the device.
- Installation on many different types of pole hardware Ø10mm min. eye or pigtail type.

Installation

- On end poles.
- When the line is at an angle greater than 15° (instead of a suspension device), in order to preserve the integrity of the cable over time.
- If road crossing (obligatory cable stop on each pole both sides of the road).
- In case of unbalanced adjacent spans (a span of 40m, followed by a range of 30m, for example).
- If rugged terrain (line mountainside down for example).
- In alignment every 5 poles (if using suspension clamp on intermediate poles) or on every poles (double anchor)



SIMPLE ANCHORING



DOUBLE ANCHORING