


ADSS Optical Fiber Cable 80m span

Cable Design

Loose Tube Optical Fiber Cable- Non-Armored -Dielectric-Dry Core-G.652D Fiber



- **Central Strength Member (CSM):** glass fiber reinforced plastic rod (FRP), with PE sheath covering when needed.
- **Loose Tube:** PBT plastic material, containing 6/12 fibers and filled with a suitable water tightness jelly.
- **Filler Elements:** PP plastic rods, when needed.
- **Stranding:** loose tube & filler stranded around the CSM.
- **Longitudinal Water Tightness:** dry core with water swellable elements (water blocking tape and yarn).
- **Ripcord:** 2 polyester ripcord under outer sheath.
- **Outer Sheath:** Black HDPE.

Cable Specification

Cable Cores		12	24	48	72	96	144
No. of Tubes		2	4	4	6	8	12
No. of Fillers		4	2	2	0		
Fiber Counts in Tube		6		12			
Tube/Filler-Φ	mm	2.2		2.4			
CSM-Φ	mm	2.3		2.5		3.3	
CSM with Coated- Φ	mm	/				4.2	7.3
Thickness of Outer PE Sheath	mm	1.6					
Max. Allowable Tensile	N	configured to customer needs					
Nominal Cable Diameter	mm	10.4		11.9		12.6	15.8
Nom. Cable Weight	Kg/km	82		92		120	188

Cable Application

Temperature Range		Minimum Bend Radius	
Transportation & Storage	-30~+70°C	Load	20×D
Operation	-30~+70°C	Unload	10×D

Main Mechanical and Environmental Characteristic

Test	Test Standard	Specified Value	Acceptance Criteria
Tensile	IEC 60794-1-2-E1	MAT, 10min	$\Delta\alpha$ reversible, fiber strain \leq 0.33%
Crush	IEC 60794-1-2-E3	2000N/10cm, 5min	$\Delta\alpha$ reversible, no damage
Impact	IEC 60794-1-2-E4	5J, R=300mm, 3times	$\Delta\alpha$ reversible, no damage
Repeated Bending	IEC 60794-1-2-E6	R=20D, 250N, 20cycles	$\Delta\alpha$ reversible, no damage
Bending	IEC 60794-1-2-E6	150N, 20cycles, +/-90°	$\Delta\alpha$ reversible, no damage
Torsion	IEC 60794-1-2-E7	2m, 5cycles, +/-180°	$\Delta\alpha$ reversible, no damage
Temperature Cycling	IEC 60794-1-2-F1	-40~+70°C, 2cycles,	$\Delta\alpha\leq$ 0.05dB/km, no damage
Water Penetration	IEC 60794-1-2-F5	3m cable, 1m water, 24h	No water leakage

ADSS Optical Fiber Cable 80m span

Cabled Fiber Performance (G.652D)

Characteristics		Acceptance Value
Attenuation	@1310nm	≤0.35dB/km
	@1383nm	≤0.34dB/km
	@1550nm	≤0.21dB/km
	@1625nm	≤0.23dB/km
Mode Field Diameter	@1310nm	9.2±0.4 μm
	@1550nm	10.4±0.5 μm
Dispersion	@1300 +30/-15nm	≤3.5ps/(nm·km)
	@1550nm	≤18ps/(nm·km)
	@1625nm	≤22ps/(nm·km)
Zero-Dispersion wavelength		1300nm~1324nm
Zero-Dispersion slope		≤0.092ps/(nm ² ·km)
Cable cutoff wavelength λ _{cc} (nm)		≤1270nm
Cladding diameter		125±0.7μm
Cladding non-circularity		≤0.7%
Core/cladding concentricity error		≤0.5μm
Fiber diameter with coating (colored)		245±10μm
Cladding/coating concentricity error		≤12.0μm
Proof stress		≥0.69GPa(100kpsi)
Dynamic stress corrosion susceptibility parameter (typical value)		≥20

Fiber and Tube Color

Color Identification of Fiber

No	1	2	3	4	5	6	7	8	9	10	11	12
Color	Red	Green	Yellow	Blue	Brown	White	Grey	Violet	Black	Orange	Aqua	Pink

Color Identification of Tube

No	1	2	3	4	5	6	7	8	9	10	11	12
Color	Red	Green	Yellow	Blue	Brown	White	Grey	Violet	Black	Orange	Aqua	Pink

Sheath Marking, Delivery Length

The outer sheath is marked in 1 meter intervals as follows:

In Accordance with Custom's Requirement

Standard delivery length will be 4 km. with -1/+3% tolerance